

SYLVANIA LED Glass Portfolio

Featuring Made in the USA with US and Global Parts products



Key Features & Benefits

- Full Lighting Portfolio: A-line, Globe, Reflector and PAR lamps*
- Select models dimmable: ULTRA A-line, ULTRA Clear Glass A-line, ULTRA G25 and Contractor BR30
- Full Glass lamp housing manufactured in the USA
- Variety of color temperatures available for specific applications
- All lamps are compliant under the Trade Agreement Act (TAA)
- PAR38, A-line, G and BR lamps are compliant under the Buy American Act (BAA-COTS item)

Assembled in our plants in St. Marys, Pennsylvania and Versailles, Kentucky and designed by our engineering team in Wilmington, Massachusetts, the SYLVANIA LED Glass Portfolio Lamps are the exceptional choice for local products. They are also an investment in more than 200 American jobs—and lamps manufactured locally can be supplied quicker. Offering full LED attributes of longer life, incandescent-shape and no-UV light make SYLVANIA LED Glass Portfolio Lamps ideal for numerous commercial and residential applications.



*Assembled in Mexico – PAR30LN and PAR20
 **25,000 hour product only

Application Information

Application Notes

1. Operating temperatures: -4°F to 104°F (-20°C to 40°C) – Contractor Series LED PAR.
2. Operating temperatures: -4°F to 113°F (-20°C to 45°C) – ULTRA A-line, Contractor Series A-line, ULTRA Clear Glass A-line, G25 and BR30 lamps.
3. Not for use with emergency light fixtures or exit lights.
4. Not for use with dimmers – Contractor Series LED A-line, G25 and PAR lamps.
5. Suitable for use in rated fixtures where protected from the weather.

A-line & G25 Applications

- Downlights
- Pendant fixtures
- Table/floor lamps – Wall sconces
- Vanity – G25

Market Segments

- Hospitality
- Offices
- Residential
- Restaurants
- Retail

BR30 Applications

- General lighting
- Recessed lighting
- Track lighting

Market Segments

- Hospitality
- Museums
- Office
- Residential

PAR Applications

- General lighting
- Recessed downlights
- Track lighting
- Wall washer

Market Segments

- Hospitality
- Offices
- Residential
- Restaurants



Ordering Information

Item Number	Ordering Abbreviation	Wattage (W)	Base Type	Replaces	Input Voltage (V)	Average Rated Life (hrs.)	CCT	Typical Lumens (lm)	CRI	Case Pack	Bulb Finish	ENERGY STAR®	TAA/BAA-COTS
ULTRA LED A-line Lamps													
74963	LED4.5A19/DIM/O/827/RP4	4.5	Medium	40W	120	25,000	2700K	450	82	16	Frosted	Yes	Both
74964	LED4.5A19/DIM/O/827/RP	4.5	Medium	40W	120	25,000	2700K	450	82	12	Frosted	Yes	Both
74965	LED4.5A19/DIM/O/850/RP4	4.5	Medium	40W	120	25,000	5000K	450	82	16	Frosted	Yes	Both
74966	LED4.5A19/DIM/O/850/RP	4.5	Medium	40W	120	25,000	5000K	450	82	12	Frosted	Yes	Both
74967	LED6.5A19/DIM/O/827/RP4	6.5	Medium	60W	120	25,000	2700K	800	82	16	Frosted	Yes	Both
74968	LED6.5A19/DIM/O/827/RP	6.5	Medium	60W	120	25,000	2700K	800	82	12	Frosted	Yes	Both
74969	LED6.5A19/DIM/O/850/RP4	6.5	Medium	60W	120	25,000	5000K	800	82	16	Frosted	Yes	Both
74970	LED6.5A19/DIM/O/850/RP	6.5	Medium	60W	120	25,000	5000K	800	82	12	Frosted	Yes	Both
40230	LED6.9A19/DIM/O/827/13USARP	6.9	Medium	60W	120	15,000	2700K	800	82	12	Frosted	Yes	Both
40231	LED6.9A19/DIM/O/827/13USARP	6.9	Medium	60W	120	15,000	2700K	800	82	16	Frosted	Yes	Both
74971	LED9A21/DIM/O/827/RP4	9	Medium	75W	120	25,000	2700K	1100	82	16	Frosted	N/A	Both
74972	LED9A21/DIM/O/827/RP	9	Medium	75W	120	25,000	2700K	1100	82	12	Frosted	N/A	Both
74973	LED9A21/DIM/O/850/RP4	9	Medium	75W	120	25,000	5000K	1100	82	16	Frosted	N/A	Both
74974	LED9A21/DIM/O/850/RP	9	Medium	75W	120	25,000	5000K	1100	82	12	Frosted	N/A	Both
74975	LED11A21/DIM/O/827/RP4	11	Medium	100W	120	25,000	2700K	1600	82	16	Frosted	N/A	Both
74976	LED11A21/DIM/O/827/RP	11	Medium	100W	120	25,000	2700K	1600	82	12	Frosted	N/A	Both
74977	LED11A21/DIM/O/850/RP4	11	Medium	100W	120	25,000	5000K	1600	82	16	Frosted	N/A	Both
74978	LED11A21/DIM/O/850/RP	11	Medium	100W	120	25,000	5000K	1600	82	12	Frosted	N/A	Both
Contractor Series LED A-line Lamps													
74955	LED4.5A19/F/827/10YV/RP4	4.5	Medium	40W	120	11,000	2700K	450	80	16	Frosted	N/A	Both
74956	LED4.5A19/F/827/10YV/RP	4.5	Medium	40W	120	11,000	2700K	450	80	12	Frosted	N/A	Both
75532	LED4.5A19/F/850/10YV/RP4	4.5	Medium	40W	120	11,000	5000K	450	80	16	Frosted	N/A	Both
75533	LED4.5A19/F/850/10YV/RP	4.5	Medium	40W	120	11,000	5000K	450	80	12	Frosted	N/A	Both
74957	LED6.5A19/F/827/10YV/RP4	6.5	Medium	60W	120	11,000	2700K	800	80	16	Frosted	N/A	Both
74958	LED6.5A19/F/827/10YV/RP	6.5	Medium	60W	120	11,000	2700K	800	80	12	Frosted	N/A	Both
75534	LED6.5A19/F/850/10YV/RP4	6.5	Medium	60W	120	11,000	5000K	800	80	16	Frosted	N/A	Both
75535	LED6.5A19/F/850/10YV/RP	6.5	Medium	60W	120	11,000	5000K	800	80	12	Frosted	N/A	Both
74959	LED9A19/F/827/10YV/RP4	9	Medium	75W	120	11,000	2700K	1100	80	16	Frosted	N/A	Both
74960	LED9A19/F/827/10YV/RP	9	Medium	75W	120	11,000	2700K	1100	80	12	Frosted	N/A	Both
75536	LED9A19/F/850/10YV/RP4	9	Medium	75W	120	11,000	5000K	1100	80	16	Frosted	N/A	Both
75537	LED9A19/F/850/10YV/RP	9	Medium	75W	120	11,000	5000K	1100	80	12	Frosted	N/A	Both
74961	LED11A21/F/827/10YV/RP4	11	Medium	100W	120	11,000	2700K	1600	80	16	Frosted	N/A	Both
74962	LED11A21/F/827/10YV/RP	11	Medium	100W	120	11,000	2700K	1600	80	12	Frosted	N/A	Both
75538	LED11A21/F/850/10YV/RP4	11	Medium	100W	120	11,000	5000K	1600	80	16	Frosted	N/A	Both
75539	LED11A21/F/850/10YV/RP	11	Medium	100W	120	11,000	5000K	1600	80	12	Frosted	N/A	Both
ULTRA LED Clear Glass A-line Lamps													
40246	LED4.5A19/DIM/CL/827/13Y/USA/RP	4.5	Medium	40W	120	15,000	2700K	450	80	12	Clear	No	Both
40247	LED4.5A19/DIM/CL/827/13Y/USA/RP4	4.5	Medium	40W	120	15,000	2700K	450	80	32	Clear	No	Both
40248	LED6.5A19/DIM/CL/827/13Y/USA/RP	6.5	Medium	60W	120	15,000	2700K	800	80	12	Clear	No	Both
40249	LED6.5A19/DIM/CL/827/13Y/USA/RP4	6.5	Medium	60W	120	15,000	2700K	800	80	32	Clear	No	Both
40250	LED9A21/DIM/CL/827/13Y/USA/RP	9	Medium	75W	120	15,000	2700K	1100	80	12	Clear	No	Both
40251	LED9A21/DIM/CL/827/13Y/USA/RP4	9	Medium	75W	120	15,000	2700K	1100	80	32	Clear	No	Both
40252	LED11A21/DIM/CL/827/13Y/USA/RP	11	Medium	100W	120	15,000	2700K	1500	80	12	Clear	No	Both
40253	LED11A21/DIM/CL/827/13Y/USA/RP4	11	Medium	100W	120	15,000	2700K	1500	80	32	Clear	No	Both
ULTRA LED G25 Lamps													
40470	LED3.5G25/F/DIM/827/GL/USA/RP	3.5	Medium	40W	120	15,000	2700K	350	80	6	Frosted	No	Both
40472	LED4.5G25/F/DIM/827/GL/USA/RP	4.5	Medium	60W	120	15,000	2700K	500	80	6	Frosted	No	Both
40469	LED3.5G25/CL/DIM/827/GL/USA/RP	3.5	Medium	40W	120	15,000	2700K	350	80	6	Clear	No	Both
40522	LED4.5G25/CL/DIM/827/GL/USA/RP	4.5	Medium	60W	120	15,000	2700K	500	80	6	Clear	No	Both
Contractor Series LED G25 Lamps													
40214	LED3G25/F/827/10YV/GL/USA/RP2	3	Medium	40W	120	11,000	2700K	300	80	12	Frosted	N/A	Both
40215	LED5G25/F/827/10YV/GL/USA/RP2	5	Medium	60W	120	11,000	2700K	550	80	12	Frosted	N/A	Both
40218	LED3G25/F/850/10YV/GL/USA/RP2	3	Medium	40W	120	11,000	5000K	300	80	12	Frosted	N/A	Both
40219	LED5G25/F/850/10YV/GL/USA/RP2	5	Medium	60W	120	11,000	5000K	550	80	12	Frosted	N/A	Both
Contractor Series LED BR30 Lamps													
75528	LED7.5BR30/DIM/827/10YV/GL/B4	7.5	Medium	65W	120	11,000	2700K	650	80	16	Frosted	N/A	Both
40049	LED7.5BR30/DIM/827/10YV/GL/RP2	7.5	Medium	65W	120	11,000	2700K	650	82	16	Frosted	N/A	Both
Double Life LED PAR Lamps*													
40245	LED12.5PAR38/830/FL30/GL/22Y/USA/RP2	12.5	Medium	90W	120	25,000	3000K	1050	80	10	–	N/A	Both
40244	LED16PAR38/830/FL30/GL/22Y/USA/RP2	16	Medium	120W	120	25,000	3000K	1300	80	10	–	N/A	Both
Contractor Series LED PAR Lamps*													
79733**	LED5.5PAR20/830/FL30/10YV/GL/RP2	5.5	Medium	50W	120	11,000	3000K	475	80	10	–	N/A	TAA
77188**	LED9PAR30LN/830/FL30/10YV/GL/RP2	9	Medium	75W	120	11,000	3000K	750	81	10	–	N/A	TAA
74771	LED7PAR38/830/FL30/10YV/GL/RP2	7	Medium	45W	120	11,000	3000K	550	80	10	–	N/A	Both
74772	LED12.5PAR38/830/FL30/10YV/GL/RP2	12.5	Medium	90W	120	11,000	3000K	1050	80	10	–	N/A	Both
74773	LED16PAR38/830/FL30/10YV/GL/RP2	16	Medium	120W	120	11,000	3000K	1300	80	10	–	N/A	Both

*30° Beam Angle 74771 CBCP 900; 74772 CBCP 1700; 74773 CBCP 2000





**PAR30LN and PAR20 Made in Mexico

How to Read Ordering Abbreviations

ULTRA LED A-line Lamps		Contractor Series LED A-line Lamps		ULTRA LED Clear Glass A-Line Lamps		ULTRA LED G25 Lamps	
LED4.5A19/DIM/0/827/RP4		LED4.5A19/F/827/10YV/RP4		LED4.5A19/DIM/CL/827/13Y/USA/RP4		LED3.5G25/F/DIM/827/GL/USA/RP	
LED	Lamp technology	LED	Lamp technology	LED	Lamp technology	LED	Lamp technology
4.5	Nominal wattage	4.5	Nominal wattage	4.5	Nominal wattage	3.5	Nominal Wattage
A19	Lamp shape	A19	Lamp shape	A19	Lamp Shape	G25	Lamp shape
DIM	Dimmable	F	Frosted	DIM	Dimmable	F	Frosted
0	Omnidirectional	827	CRI: 80+; CCT: 2700K	CL	Clear	DIM	Dimmable
827	CRI: 80+; CCT: 2700K	10YV	11,000 hour life	827	CRI: 80+ CCT: 2700K	827	CRI: 80+ CCT: 2700K
RP4	4pk	RP4	4pk	13Y	15,000 hour life	GL	Glass
				USA	Made in USA	USA	Made in USA
				RP4	4pk	RP	1pk

Contractor Series LED G25 Lamps		Contractor Series LED BR30 Lamps		Double Life LED PAR Lamps		Contractor Series LED PAR Lamps	
LED3G25/F/827/10YV/GL/USA/RP2		LED7.5BR30/DIM/827/10YV/GL/B4		LED16PAR38/830/FL30/GL/22Y/USA/RP2		LED16PAR38/830/FL30/10YV/GL/RP2	
LED	Lamp technology	LED	Lamp technology	LED	Lamp technology	LED	Lamp technology
3	Nominal wattage	7.5	Nominal wattage	16	Nominal wattage	16	Nominal wattage
G25	Lamp shape	BR30	Lamp shape	PAR38	Lamp shape	PAR38	Lamp shape
F	Frosted	DIM	Dimmable	830	CRI: 80+; CCT: 3000K	830	CRI: 80+; CCT: 3000K
827	CRI: 80+; CCT: 2700K	827	CRI: 80+; CCT: 2700K	FL30	Flood 30° beam angle	FL30	Flood 30° beam angle
10YV	11,000 hour life	10YV	11,000 hour life	22Y	25,000 hour life	10YV	11,000 hour life
GL	Glass	GL	Glass	GL	Glass	GL	Glass
USA	Made in USA	B4	4pk	USA	Assembled in USA	RP2	2pk
RP2	2pk			RP2	2pk		


Lamp Dimensions

ULTRA LED A-line Lamps				
	(A) MOL inches (mm)	(B) Diameter inches (mm)		
LED4.5A19	4.3 (109)	2.36 (60)	A19	A21
LED6.5A19	4.3 (109)	2.36 (60)		
LED6.9A19	4.3 (109)	2.36 (60)		
LED9A21	5.17 (131)	2.56 (65)		
LED11A21	5.17 (131)	2.56 (65)		
Contractor Series LED A-line Lamps				
	(A) MOL inches (mm)	(B) Diameter inches (mm)		
LED4.5A19	4.3 (109)	2.36 (60)	A19	A21
LED6.5A19	4.3 (109)	2.36 (60)		
LED9A19	4.3 (109)	2.36 (60)		
LED11A21	5.17 (131)	2.56 (65)		

Lamp Dimensions (continued)


ULTRA and Contractor Series LED G25 Lamps

Lamps	(A) MOL inches (mm)	(B) Diameter inches (mm)
LEDG25	4.4 (112)	3.09 (78.4)




Contractor Series LED BR30 Lamps

Lamps	(A) MOL inches	(B) Diameter inches
LED7.5BR30	5.20	3.69




Double Life & Contractor Series LED PAR Lamps


Lamps	(A) MOL inches	(B) Diameter inches
PAR20	3.25	2.5
PAR30LN	4.69	3.75
PAR38	5.3	4.75



PAR20



PAR30 LN



PAR38

LEDVANCE LLC
 200 Ballardvale Street
 Wilmington, MA 01887 USA
 Phone 1-800-LIGHTBULB (1-800-544-4828)
www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.
 All other trademarks are those of their respective owners.
 Licensee of product trademark SYLVANIA in general lighting.
 Specifications subject to change without notice.

[/sylvania](https://twitter.com/sylvania) [/sylvania](https://facebook.com/sylvania)

